

INDUSTRIAL RACK-MOUNT LCD KVM DRAWER

SK SERIES 1U Rack-mount LCD Drawer

SK525A-15 SK585A-15 SK595A-15
SK525A-17 SK585A-17 SK595A-17



- SK525A-15
- SK525A-17



- SK585A-15
- SK585A-17



- SK595A-15
- SK595A-17

KEY FEATURES

- One set built-in keyboard, touch pad & monitor.
- Heavy-duty steel.
- With high brightness 15" or 17" TFT LCD Panel.
- Anti-glare tempered glass for added protection to the LCD screen. (Optional)
- Mechanic or Membrane (Optional) Multi-Language keyboard in 105 keys. With touch pad.
- Built-in rail with self-locking device
- Standard KVM cable

WITH 8 OR 16 PORT KVM SWITCH

- Support DOS, Windows OS, Netware, SCO Unix, HP Unix, Linux.
- Easy PC selection via ON Screen Display Manual.
- Support eight characters password protection and search PC server name.
- Extra cascade port.
- Auto scan mode for monitoring PCs.
- 3 in 1 KVM cable.

SPECIFICATION

Spec.	Model	SK525A-15	SK585A-15	SK595A-15	SK525A-17	SK585A-17	SK595A-17
Size		442.4(W) 44.0(H) 480(D)	442.4(W) 44.0(H) 620(D)		442.4(W) 44.0(H) 515(D)	442.4(W) 44.0(H) 655(D)	
Weight		10Kgs	11Kgs	12Kgs	11Kgs	13Kgs	
Monitor		15" TFT LCD, 1024x768, 250 nits, 120/120 viewing angle, contrast ratio 350:1, Number of colors: 16.2M Backlight MTBF: 50,000 hours under 25±5°C			17" TFT LCD, 1280x1024, 300 nits, 160/160 viewing angle, contrast ratio 450:1, Number of colors: 16.2M Backlight MTBF: 50,000 hours under 25±5°C		
Keyboard/Mouse		Mechanic keyboard in 105 keys, with touch pad					
Console port		1	1	1	1	1	1
PC port		NA	8	16	NA	8	16
Max. Connected PCs		NA	120	128	NA	120	128
Port selection		OSD (On Screen Display) Hot Key Pushbutton switch			OSD (On Screen Display) Hot Key Pushbutton switch		
Console Connection (All Female type)		PS/2 Keyboard Mini Din 6 pin PS/2 Mouse Mini Din 6 pin VGA HDDB 15 pin			PS/2 Keyboard Mini Din 6 pin PS/2 Mouse Mini Din 6 pin VGA HDDB 15 pin		
Daisy Chain Connection (All Female type)		PS/2 Keyboard Mini Din 6 pin PS/2 Mouse Mini Din 6 pin VGA HDDB 15 pin			PS/2 Keyboard Mini Din 6 pin PS/2 Mouse Mini Din 6 pin VGA HDDB 15 pin		
KVM Cable Length		1.8M	3M	5M	1.8M	3M	5M

SK SERIES
1U Rack-mount LCD 2 Console KVM Drawer



SK585B-15 SK595B-15
SK585B-17 SK595B-17



- SK585B-15
- SK585B-17

- SK595B-15
- SK595B-17

INTRODUCTION

The Industrial KVM Switch Solution provides high efficiency in server management. Integrated with a keyboard, mouse, TFT LCD panels and OSD KVM Switch in an industry standard 19" 1U-height rack drawer, it saves equipment space and able to control multiple servers.

With dual KVM access built-in the 8/16-Port KVM Switch, you can reach your servers not only in the rack, but also outside the rack. You can use optional extension cable, UTP KVM Extender, or IP KVM to setup your second access anywhere. This centralized control is ideal solution in server management.

WITH 8 OR 16 PORT KVM SWITCH

- Support DOS, Windows OS, Netware, SCO Unix, HP Unix, Linux, FreeBSD, IBM6000, Open VMX
- Easy PC selection via ON Screen Display Manual.
- Auto scan mode for monitoring PCs.
- SK585B and SK595B are build-in 8/16 Port OSD KVM Switch to connect 8/16 PS/2 based servers.
- Support DDC2B, correct Monitor type detection for each port.
- Full function OSD menu and able to stack same series KVM to expand PC control.
- The second console for extending the control by KVM cable, UTP KVM Extender, IP KVM.....etc.
- Optional interface coverter for SUN/USB computer.
- Can use the Logitech touchpad and mechanic keyboard.
- 3 in 1 KVM cable.

SPECIFICATION

Spec.	Model	SK585B-15	SK595B-15	SK585B-17	SK595B-17		
Size		442.4(W) 44.0(H) 620(D)			442.4(W) 44.0(H) 655(D)		
Weight		11Kgs	12Kgs	13Kgs			
Monitor		15" TFT LCD, 1024x768, contrast ratio 300:1, Brightness 200~250 de/m2, Backlight MTBF:30,000 hours, Built-in multi language OSD controls, Automatic flat panel shut-off when KVM drawer is in closed position, or signal input			17" TFT LCD, 1280x1024, 300 nits, 160/160 viewing angle, contrast ratio 450:1, Number of colors:16.2M Backlight MTBF:50,000 hours under 25±5°C		
Keyboard/Mouse		Mechanic keyboard in 105 keys, with touch pad					
Console port		2	2	1	1		
PC port		8	16	8	16		
Max, Connected PCs		2048	4096	2048	4096		
Port selection		OSD (On Screen Display) Hot Key Pushbutton switch			OSD (On Screen Display) Hot Key Pushbutton switch		
Console Connection		PS/2 Keyboard Mini Din 6 pin PS/2 Mouse Mini Din 6 pin VGA HDDB 15 pin			PS/2 Keyboard Mini Din 6 pin PS/2 Mouse Mini Din 6 pin VGA HDDB 15 pin		
Daisy Chain Connection		Integrated HD-DB15 connection (KVM Port)			Integrated HD-DB15 connection (KVM Port)		
KVM Cable Length		1.8M	3M	6M	9M	15M	30M